



SAVE THESE INSTRUCTIONS - READ ALL INSTRUCTIONS CAREFULLY

WARNING



CAN ICES-005 (B) / NMB-005 (B)

PLEASE READ ALL INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION.

- To prevent personal injury or product damage only licensed electricians/personnel should install fixture.
- To avoid electric shock or component damage disconnect power before attempting installation or servicing.
- This product must be installed in accordance with the National Electric Code (NEC) and all applicable Federal, State/Provincial and Local Electric Codes and Safety Standards.
- Disconnect fixture and allow cooling prior to servicing.
- Any alteration or modification of this product is expressly forbidden as it may cause serious personal injury, death, property damage and/or product malfunction.
- To prevent product malfunction and/or electrical shock this product must be properly grounded.
- All parts must be used as indicated in the instructions. Do not substitute any parts, leave parts out, or use any parts that are worn, damaged or broken.
- **NOTE:** This fixture will only work with 120VAC input power supply. Any other power supply may damage or destroy it.

Complies With CAN ICES-005 (B) / NMB-005 (B)

INSTALLATION INSTRUCTION

1. Before installation, remove the luminaire and accessories package from the carton. Remove the plastic lens from the luminaire as per figure #1.
2. Thread the enclosed mounting screws into junction box mounting holes, and partially tighten the screws.
3. Pull the power supply wires out from the junction box. Using wire nuts, connect the black supply wire (hot) to the black luminaire wire, the white supply wire (neutral) to the white luminaire wire, the supply ground wire to the green luminaire wire. Wrap all wire connections with electrical tape for a secure connection.
4. After all wiring connections are secure, install the metal luminaire housing to the junction box by sliding the housing keyhole slots over the mounting screws. Rotate the luminaire housing clockwise until the screws slide into the narrow ends of the keyhole slots. Securely tighten the mounting screws.
5. Select the color temperature you need, and set the code switch to corresponding color temperature position. Default setting is 4000K
6. Reattach lens as per Figure #1.
7. When the installation is complete, the luminaire should appear flush to the ceiling.

- **TURN ON** the electrical supply after installation is complete.
 - Turn the light switch **ON** to activate the luminaire.
- For non-user replaceable light sources: "The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person."

