



PRODUCT CODE: FLM4-8035N-BL-YK

LED FLOOD LIGHT/ YOKE BRACKET



## PRODUCT DESCRIPTION

The Etlin-Daniels FLM4-8035N-BL-YK LED Flood fixture offers the latest in both design and energy efficient performance. With its reduced size and textured architectural powdercoat finish, it will compliment a wide range of industrial, residential and commercial applications. The durable and watertight casting along with the tempered glass lens allow for long and energy efficient life. Fixtures available with either yoke or knuckle mount.

## FEATURES


- LED Outdoor Light Source
- Textured Architectural Powdercoat finish
- Tempered glass lens
- Removable back cover for easy installation
- Yoke bracket with watertight cord grip installed
- Suitable for wet location
- 15" - 20" lead lengths
- Non-Dimmable
- 5 year warranty
- L70 - 50,000 hours

## PRODUCT SPECIFICATIONS (OPTICAL DATA)

## PRODUCT SPECIFICATIONS (ELECTRICAL DATA)

LED TYPE	LED QTY	SYSTEM EFFICACY	LUMENS	COLOR TEMPERATURE	BEAM ANGLE	CRI	SYSTEM EFFICIENCY	VOLTAGE	POWER FREQ.	POWER EFFICIENCY	POWER FACTOR	HARMONIC DISTORTION
PHILIPS 3030	72 CHIPS	95LM/W	7849.6LM	5000K	105±10°	>80CRI	>89%	AC347V	50-60HZ	>89%	>0.90	<15%

## PRODUCT SPECIFICATIONS

WATTAGE	FIXTURE MATERIAL	INGRESS PROTECT	LIFE SPAN	STORAGE TEMP	OPERATING TEMP	PRODUCT DIMENSIONS	CARTON SIZE	
80W	DIE CAST ALUMINUM/BLACK	IP65	>50,000 HOURS	-25°C~-80°C -13°F~-176°F	-40°C~-40°C -40°F~-104°F	9.25 X 8.07 X 4.25 INCHES (235 X 205 X 108 MM)	12.13 X 8.82 X 5 INCHES (308 X 224 X 127 MM)	

## ADDITIONAL INFORMATION

### INSTALLATION METHOD

YOKE MOUNT

### FIXTURE COLOR

ALUMINUM BODY/BLACK


### CONTROL TYPE

NON-DIMMABLE


**PRODUCT CODE: FLM4-8035N-BL-YK LED FLOOD LIGHT/YOKE BRACKET**

**LUMINAIRE PHOTOMETRIC (TEST REPORT)**

**ILLUMINANCE (AT A DISTANCE) - FLUX OUT: 6432LM**

3.28FT 1M	1081,3315LX		8.83FT 2.69M
6.56FT 2M	270.2,828.8LX		17.68FT 5.39M
9.84FT 3M	120.1,368.3LX		26.51FT 8.08M
13.12FT 4M	67.54,207.2LX		35.33FT 10.77M
16.40FT 5M	43.23,132.6LX		44.16FT 13.46M
19.69FT 6M	30.02,92.09LX		53.02FT 16.16M
22.97FT 7M	22.05,67.66LX		61.84FT 18.85M
26.25FT 8M	16.89,51.80LX		70.67FT 21.54M
29.52FT 9M	13.34,40.93LX		79.49FT 24.23M
32.80FT 10M	10.81,33.15LX		88.35FT 26.93M
<b>HT</b>	<b>EAVG/EMAX</b>	<b>ANGLE: 106.79DEG</b>	<b>DIA</b>

**ISOCANDELA DIAGRAM (PERCENT OF MAXIMUM INTENSITY)**



**CERTIFICATIONS**



**DRIVER/LED CHIP**



**ORDERING INFORMATION - FL4 SERIES**

SERIES	SIZE	DLC TYPE	WATTAGE	VOLTAGE	COLOR TEMPERATURE	DIMMABLE	FINISH	BRACKET
E.G. FL	M	4	80	3	5	N N - NO	BL	YK
FL - FLOOD LIGHT	M - MEDIUM	4 - DLC4.0	80 - 80W	3 - 347V	5-5000K		BL - BLACK	YK - YOKE BRACKET

Head Office - 1850 Wilson Ave. · Toronto, ON · M9M 1A1 · Tel: 416.741.7336 · Fax: 416.741.9104

Toll Free: in Canada. 1.800.661.9610 · in USA. 1.888.762.5384 (SOCKETS4U)

www.etlin-daniels.com · For sales/service questions - sales@etlin.com