

INSTALLATION FOR LED VAPOR TIGHT VPT-20U5N-FGR

SAVE THESE INSTRUCTIONS - READ ALL INSTRUCTIONS CAREFULLY

⚠ WARNING



PLEASE READ ALL INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION.

- To prevent personal injury or product damage only licensed electricians/personnel should install fixture.
- To avoid electric shock or component damage disconnect power before attempting installation or servicing.
- This product must be installed in accordance with the National Electric Code (NEC) and all applicable Federal, State/Provincial and Local Electric Codes and Safety Standards.
- Disconnect fixture and allow cooling prior to servicing.
- Any alteration or modification of this product is expressly forbidden as it may cause serious personal injury, death, property damage and/or product malfunction.
- To prevent product malfunction and/or electrical shock this product must be properly grounded.
- Selected fixture voltage must match supply line voltage.

MOUNTING INSTALLATION INSTRUCTIONS - (SAVE INSTRUCTIONS FOR FUTURE REFERENCE).

1. Use approved connectors to connect fixture wire (1) to supply wire.
2. Attach supplied gasket between fixture and wall junction box.
3. Insert the retaining screws (2) into the predrilled holes and use silicone sealant around the housing.

APPLICATIONS:

- Suitable for wet location
- Wall mounting fixture

